



Security Management System

Model S1326

HID ProxCard II

Overview

The RF-programmable S1326 proximity access control card is the industry choice for a cost effective solution. This card comes standard with our company logo or can be ordered with pre-printed custom artwork. A PVC direct print overlay, can be adhered to the card for on-site photo ID badging.



FEATURES & BENEFITS

- 125kHz proximity RF-programmable
- Universal compatibility with all HID readers
- Made from a durable PVC plastic packaging and provide a consistent read range
- Provides external number for easy identification and administration control
- Over 137 billion unique codes are available
- The cards are Passive (no batteries) and provide a long life with infinite reads

SPECIFICATIONS:

- Dimensions: 3.375" x 2.125" x .070" max
- Operating temperature: -50F to 160F
- Weight: .24 oz.
- Vertical slot punch
- Read ranges: HID MiniProx reader - up to 5.5"
HID ThinLine II reader - up to 5.5"
HID ProxPoint Plus reader - up to 3"
HID ProxPro reader - up to 8"
HID MaxiProx reader - up to 24"

ORDERING INFORMATION:

- S1326 - ProxCard II Proximity Card
- S1324C - Clear Overlay
- S1324G - Direct Print Overlay



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com