



# Model SMR10 and SMR20

## Magnetic Stripe Readers

### Overview

The SMR10 Mercury Magnetic Stripe Reader has a slim, mullion style design. The die cast metal housing makes it ideal for indoor or outdoor applications.

The SMR20 Mercury Magnetic Stripe Reader has a slim, mullion style design. The die cast metal housing makes it ideal for indoor or outdoor applications. The keypad is a 12 position membrane style.



### FEATURES & BENEFITS

- Rugged Metal Housing
- All stainless steel hardware is standard
- Audiovisual indication provides Two LED's (red/green) and beeper sounds
- Static Discharge Protection
- Accepts low or high coercivity-magnetic cards
- Standard Track 2 encoding (Track 1 & 3 are available)
- One security screw mounting
- Supports Wiegand or Clock & Data interface formats via Dip Switches

### SPECIFICATIONS:

- Dimensions: 1.95"W x 1.3"H x 5.5"L
- Power requirements: 5 or 12 VDC
- Power consumption 20 mA at 12 VDC
- Operating temperature: -40F to 170F
- Weight: 10 oz.
- Cable distance: 500' with 18AWG 6 conductor stranded with overall shield

### ORDERING INFORMATION:

SMR10 - 5 VDC standard, Magnetic Stripe Card Reader (specify black or beige)

SMR10-12V - 12 VDC Magnetic Stripe Card Reader (specify black or beige)

SMR20 - 5 VDC standard, Magnetic Stripe Card Reader w/keypad (specify black or beige)

SMR20-12V - 12 VDC Magnetic Stripe Card Reader w/ keypad (specify black or beige)

